

STARPRIM



Series N



Models



25-SB-015




25-SB-025



25-SB-035



25-SB-055



25-SB-085



25-SB-095

**Certified according to EN 1143-1
Security grade N**

- ④ Three-way locking mechanism with square bolts: 40×10 mm.
- ④ A continuous formed dog bar on the hinge side protects the safe in event of attack.
- ④ The door-frame is equipped with fire-resistant washer which protects safe interior against dust and direct irruption of flame, smoke and gases.
- ④ All safe models are able to be secured to a floor. Also provision for snap-off detector is installed.
- ④ Shelves are adjustable to every 50 mm.
- ④ The hinges enable 205° door opening for full access.
- ④ Optimal File capacity. File acc. to DIN 821-D1-80 ($w_1=75$ mm).

④ **Measurements**

STARPRIM

MODEL	* External dimensions			Internal dimensions			Weight Approx. [kg]	Volume Approx. [liters]	Max. No. of Files
	Height [mm]	Width [mm]	Depth [mm]	Height [mm]	Width [mm]	Depth [mm]			
25-SB-015	395	325	300	334	275	180	69	17	-
25-SB-025	395	405	345	334	355	225	88	27	-
25-SB-035	395	405	425	334	355	305	105	36	4
25-SB-055	570	405	425	509	355	305	132	55	4
25-SB-085	570	505	495	509	455	375	168	87	6
25-SB-095	755	505	425	694	455	305	189	96	12

- * - 45 mm extra depth with handle and different locks.
- Standard locking: 1 mechanical key lock, according to EN 1300 Grade A
- Double locking is not possible by models in security grade N.
- Optional locks, inside equipment and additional equipment are evident from special STARPRIM Specification.

